

MADE IN FRANCE
MANUFACTURER SINCE 1964



NOUVEAUTÉS • NEW • NEUHEITEN



INVEST IN THE FUTURE



Chargers, Boosters & Starters

Catalogue Chargeurs • Batterieservicegeräte-Katalog • Catálogo de Cargadores

2014B

www.gys.fr


CHARGERS • BOOSTERS • STARTERS • TESTERS • JUMPER CABLES • ACCESSORIES

Export in 104 Länder

Your Charger Partner
Votre Partenaire Chargeur
Produktvielfalt, die Überzeugt



Société familiale
Family firm
Familienbetrieb



Logistique
Logistics
Logistik



A collection of electronic testing equipment including multimeters, a power supply, and various test leads. The items are arranged on a blue gradient background. From left to right, there are several sets of red and black test leads, a small digital multimeter (DMM) showing 9.56, a larger digital multimeter (DMM) showing 12.70V, a power supply unit with two output terminals, and a black rectangular device with a grid of holes, possibly a test board or a component.



W 25

4A	12V
ENERGY 126	



Ref. **023215**
 Ref. **025141**

Ref. **023222**
 Ref. **025165**



W2



9/17 A	12V
START UP 80	

Ref. 024922  Ref. 025127

=

CHARGE
+
TEST
+
START



3,5/7 A	12V
TCB 120	



Ref. **023253**
 Ref. **025189**

Ref. **023260**
 Ref. **025202**

Ref. **023284**
 Ref. **025240**



PATENTS REGISTERED NUMBERS
001652090-0001
EUROPEAN TRADEMARK & DESIGN

TCB 60/90/120

TCB 60/90/120



Fuse X10

10A : Ref.054530
15A : Ref.054493

							CHARGE 			START 				 Recommendation							CHARGER + TESTER	BOOST	 Bzz CONTROL
		50 / 60 Hz			 Reg	Efficace / RMS	Moyen / Average (EN 60335)	1V/C	Fuse							Essence • Petrol • Benzin			Diesel				
ENERGY 124	023215		025141	230V	70W	12V	—	4,5 A	3 A	—	10 A	11,5 x 16 x 22 cm	2,2 kg	ENERGY 124				10 > 45 Ah			—	—	—
ENERGY 126	023222		025165	230V	90W	12V	—	6 A	4 A	—	10 A	11,5 x 16 x 22 cm	2,2 kg	ENERGY 126				15 > 60 Ah			—	—	—
TCB 60 automatic	023253		025189	230V	85W	12V	2	6 A	2 - 4 A	—	10 A	12 x 17 x 29 cm	2,7 kg	TCB 60 automatic		15 > 60 Ah					OK	—	OK
TCB 90 automatic	023260		025202	230V	120W	12V	2	8 A	2 - 5,5 A	—	15 A	12 x 17 x 29 cm	3,4 kg	TCB 90 automatic		15 > 90 Ah					OK	—	OK
TCB 120 automatic	023284		025240	230V	150W	12V	2	10,5 A	3,5 - 7 A	—	15 A	12 x 17 x 29 cm	3,2 kg	TCB 120 automatic					30 > 120 Ah		OK	—	OK
START UP 80 automatic	024922		025127	230V	350W	12V	2	13,5-25 A	9 - 17 A	50 A	—	12 x 18 x 32 cm	4,4 kg	START UP 80 automatic					45 > 170 Ah		OK	OK	OK

CHARGERS
HF • INVERTER




0,75 A 6/12V
GYS TECH 750

Ref. 024977



GO > 7,5 V (12V)
> 3,75 V (6V)



3,8 A 12V
GYS TECH 3800

Ref. 024939




COLD CHARGE
< 0°C > 0°C
GO > 7,5 V



3,5/7 A 12/24V
GYS TECH 7000

Ref. 024953




COLD CHARGE
< 0°C > 0°C
GO > 16 V (24V)
> 4,5 V (12V)



PRODUCT LINE

				CHARGE			Recover	Fuse		
					Efficace / RMS	Moyen / Average (EN 60335)				
GYS TECH 750	024977	230V	16,5W	6 / 12V	0,75 A	0,75 A	—	—	12 x 16 x 24 cm	0,3 kg
				12V	0,8 - 3,8 A	0,8 - 3,8 A	—	10 A	10 x 27,5 x 26 cm	0,7 kg
				12V	7 A	7 A	•	10 A	10 x 31 x 29 cm	1,3 kg
GYS TECH 3800	024939	230V	60W	24 V	3,5 A	3,5 A				
GYS TECH 7000	024953	230V	160W							

i Recommendation										  ...	IP
		Essence • Petrol • Benzin					Diesel			Supply 5 A 12V DC	
GYS TECH 750		1,2 > 20 Ah								—	IP 60
GYS TECH 3800		Charge 1,2 > 60 Ah (Maintenance 1,2 > 120 Ah)								—	IP 65
GYS TECH 7000							12 V : Charge 14 > 130 Ah (Maintenance 14 > 230 Ah)			•	IP 65
							24 V : Charge 14 > 60 Ah (Maintenance 14 > 120 Ah)				



BEST QUALITY !

4 A 12V
GYSFLASH 4A

Ref. 029156

NEW
03/2014



7 A 12V
GYSFLASH 7A

Ref. 029187



					Start mini	Moyen / Average (EN 60335)	Boost	Equalize/Absorption		Floating		
GYSFLASH 4A	029156	170 > 260V	90W	12V	1V	0,8 - 3,6A	4 A	14,6V (T > 0°)	15V (T < 0°)	13,6V	36 x 18,5 x 7 cm	0,85 kg
GYSFLASH 7A	029187	170 > 260V	160W	12V	1V	0,8 - 5 A	7 A	14,6V (T > 0°)	15V (T < 0°)	13,6V	38,5 x 20,5 x 7 cm	1,06 kg

Recommendation										IP	
GYSFLASH 4A	12V	On board/Embarqué 1,2 > 70 Ah (Maintenance 1,2 > 130 Ah)								IP 65	Automatic
GYSFLASH 7A	12V	On board/Embarqué 1,2 > 130 Ah (Maintenance 1,2 > 230 Ah)								IP 65	Automatic

CHARGERS HF • INVERTER




p. 35

2/12A 12V
GYSTECH 12/12

Ref. 024984

GO > 5V



CHARGERS HF • INVERTER ON BOARD



GO > 1V



Résine/Resin/Harz/Resina
**VIBRATIONS / VIBRATIONEN / VIBRATIONES
PROTECTED**



**ULTRA
SHOCK RESISTANT**

5A 12V
INVERTER 5HF

Ref. 029170

**IP 67
ALUMINIUM
CASE**

**RENAULT
1096600**



Fuse X10 (for accessories)
10A : Ref.054530

CHARGERS TRADITIONAL



p. 35



9A 12/24V
CT 160

Ref. 024106

Ref. 025325



12A 12/24V
CT 210

Ref. 024113

Ref. 025349



Fuse X10
15A : Ref.054493
(CT 160)
20A : Ref.054509
(CT 210)



PRODUCT LINE



CT 160 12V 24V
CT 210 12V 24V



(12V) 25 > 160 Ah
(24V) 15 > 90 Ah
(12V) 35 > 210 Ah
(24V) 20 > 100 Ah

				CHARGE				Fuse		
				12/24V	12V	24V	Efficace / RMS			
CT 160	024106	025325	230V, 50/60 Hz	190W	12V > 2	24V > 2	13,5 A	7 A	15 A	20,5 x 30 x 13,5 cm
CT 210	024113	025349	230V, 50/60 Hz	260W	12V > 2	24V > 2	18 A	8 A	20 A	22,5 x 33,5 x 14,5 cm

 Recommendation										IP	
GYSTECH 12/12		12V : Charge 2 > 200 Ah (Maintenance 2 > 250 Ah)								IP 20	•
INVERTER 5HF		On board/Embarqué 20 > 100 Ah (Maintenance 20 > 160 Ah)									—

GYSTECH 12/12	024984	230V	200W	12V	5V	2 A-12 A	—	—	22 x 26,5 x 8 cm	1,2 kg
INVERTER 5HF	029170	230V	80W	12V	1V	5 A	14,8V (liquid)	13,8V	20,5 x 12,5 x 7 cm	0,9 kg

7 A	6/12V
BATIUM 7/12	
Ref. 024496	Ref. 024557






7 A	6/12/24V
BATIUM 7/24	
Ref. 024502	Ref. 024625





25 A	6/12/24V
BATIUM 25/24	
Ref. 024533	Ref. 024618



Specific charge
Traction batteries



SMART CHARGERS AUTOMATIC



15 A	6/12V
BATIUM 15/12	
Ref. 024519	Ref. 024632



15 A	6/12/24V
BATIUM 15/24	
Ref. 024526	Ref. 024588



Fuse X10

15A : Ref.054493
(BATIUM 7/12 & 7/24)

30A : Ref.054523
(BATIUM 15/12 & 15/24)




		50 / 60 Hz			CHARGE									
					Reg	Efficace / RMS	Moyen / Average (EN 60335)			Fuse				
							Reg 1	Reg 2	boost					
BATIUM 7/12	024496	024557	230V	105W	6/12V	2	11 A	3 A	7 A	15 A	21 x 34 x 13 cm	4,8 kg	—	—
BATIUM 7/24	024502	024625	230V	210W	6/12/24V	2	11 A	3 A	7 A	15 A	21 x 34 x 13 cm	5,7 kg	—	—
BATIUM 15/12	024519	024632	230V	225W	6/12V	3	22 A	7 A	10 A	15 A	21 x 36 x 14 cm	5,9 kg	—	—
BATIUM 15/24	024526	024588	230V	450W	6/12/24V	3	22 A	7 A	10 A	15 A	21 x 36 x 14 cm	8,5 kg	—	—
BATIUM 25/24	024533	024618	230V	1150W	6/12/24V	3	37 A	7 A	15 A	25 A	28 x 42 x 23 cm	13,4 kg	—	—

Recommendation														
BATIUM 7/12	6V 12V	—	—	—	—	—	—	—	—	—	—	—	—	—
BATIUM 7/24	6V 12V 24V	—	—	—	—	—	—	—	—	—	—	—	—	—
BATIUM 15/12	6V 12V	—	—	—	—	—	—	—	—	—	—	—	—	—
BATIUM 15/24	6V 12V 24V	—	—	—	—	—	—	—	—	—	—	—	—	—
BATIUM 25/24	6V 12V 24V	35 > 180 Ah	—	—	—	—	—	—	—	—	—	—	—	—


**AUTO
DETECT**

**MICRO-PROCESSOR
CONTROL**




Protection
for on-board
electronics

**PFC POWER FACTOR
CORRECTION**



185V
265V
100m

TECHNOLOGY & ADVANTAGES



100%
<90%

50% de gain de temps
+ batterie chargée à 100%

50% of time saved
+ battery 100% charged

50% Zeitersparnis
+ 100% Vollladung


ahorro de tiempo de 50%
+ batería cargada a los 100%

HIGH EFFICIENCY
Up to 15%
Energy Saving

93%

EMC class B






I REGULATED
IuOu
FAST CHARGE

ex. Battery 12V

EASY MODE





FAN LESS
TECHNOLOGY



AUTO-RESTART



**SULPHATED
BATTERIES**

**AUTOMATIC
RECOVERY**



MADE IN FRANCE

CHARGE 12V
LIQUID 70Ah

MODE **SELECT** **START STOP**

Select mode

- Charge
- Diag / Diag +
- Showroom
- Change battery
- Configuration


Select parameters

- Voltage
- Capacity
- Battery type
- Language
- ...


Adjust values

- V
- Ah
- Liquid / Gel / Easy mode
- ...

CHARGE




DIAG




13,5 V

DIAG +




12 > 14,8 V

SHOWROOM



CHANGE BATTERY



CHARGERS & BSU (BATTERY SUPORT UNITS)



Tablette - Wall support
Halterung




Ref. 054592



**Chariot
Trolley
Fahrwagen**

Ref. 054608

**Fuse Kit
40 A
054646**



30 A 12 V
**GYSFLASH
30.12 HF**
Ref. 029224




30 A 12/24V
**GYSFLASH
30.24 HF**
Ref. 029231



10,5 cm




10,5 cm



					START MINI	Imax 100% @40°C	CHARGE		BSU				Fuse			 Recommendation	  	    
					 Charging Curve	Diag	Diag+	SHOWROOM	Change Battery									
GYSFLASH 30.12HF	029224	230 V	12V	500 W	2 V	30 A	10>400 Ah	IUoU	13,5 V	12>14,8 V	12>14,8 V	12,9 V	40 A	25,5 x 23 x 10,5 cm	3,8 kg	GYSFLASH 30.12HF		10 > 400 Ah
GYSFLASH 30.24HF	029231	230 V	12V	500 W	2 V	30 A	10>400 Ah	IUoU	13,5 V	12>14,8 V	12>14,8 V	12,9 V	40 A	25,5 x 23 x 10,5 cm	3,8 kg	GYSFLASH 30.24HF	 	12 V : 10 > 400 Ah 24 V : 10 > 200 Ah
			24V			15 A	10>200 Ah		—	—	—	25,8 V						

14

TRADITIONAL
STARTERS
& CHARGERS



430 A

12/24V

PROSTART 430

Ref. 025219

United Kingdom Ref. 025226

610 A

12/24V

PROSTART 610

Ref. 025257

United Kingdom Ref. 025264

420 A

12/24V

NEOSTART 420

Ref. 025295

United Kingdom Ref. 025479

620 A

12/24V

NEOSTART 620

Ref. 025288

United Kingdom Ref. 025486



Fuses 200 A x 2
Ref. 054547



Fuses 200 A x 2
Ref. 054547

			50/60 Hz			CHARGE					START						Recommendation		50 Ah > > > > 100 Ah > > > > 150 Ah > > > > 200 Ah			
							Efficace / RMS	Moyen / Average (EN 60335)	Automatic	pos. Manual		min > max	1V/C						0V/C			
PROSTART 430	025219 025226	230V	16A	12/24V	3	52 A	35 A	—	•	20 > 700 Ah	250 A	430 A	—	31 x 36,5 x 65 cm	23 kg	PROSTART 430						
PROSTART 610	025257 025264	230V	16A	12/24V	3	72 A	45 A	—	•	20 > 1000 Ah	400 A	610 A	—	31 x 36,5 x 65 cm	26,5 kg	PROSTART 610						
NEOSTART 420	025295 025479	230V	16A	12/24V	3	70 A	45 A	—	•	20 > 1000 Ah	300 A	420 A	—	47 x 32 x 27 cm	20,5 kg	NEOSTART 420						
NEOSTART 620	025288 025486	230V	16A	12/24V	3	90 A	60 A	—	•	20 > 1350 Ah	360 A	620 A	—	47 x 32 x 27 cm	24 kg	NEOSTART 620						

AUTOMATIC
STARTERS
& CHARGERS




&

CHARGE

ELECTRONIC
CONTROL

MANUAL



235 A 12V
GYSTART 235

Ref. 025318

600 A 12V
GYSTART 612 E

Ref. 025332



5m

700 A 12/24V
GYSTART 724 E

Ref. 025356



5m

900 A 12/24V
GYSTART 924.230

Ref. 025363



5m

1 200 A 12/24V
GYSTART 1224 T

Ref. 025394



5m



Fuses 200A x 2
Ref. 054547

					CHARGE				START				Recommendation		50 Ah > > > > 100 Ah > > > > 150 Ah > > > > 200 Ah			
						Efficace / RMS	Moyen / Average (EN 60335)	Automatic	pos. Manual	min > max	1V/C	0V/C						
GYSTART 235	025318	230V	16A	12V	2	25 A	17 A	•	•	20 > 400 Ah	140 A	235 A	—	24 x 18 x 35 cm	10,1 kg	GYSTART 235		
GYSTART 612 E	025332	230V	16A	12V	ELECTRONIC 10/45	70 A	45 A	•	•	20 > 1000 Ah	350 A	600 A	•	31 x 36,5 x 65 cm	25,5 kg	GYSTART 612 E		
GYSTART 724 E	025356	230V	16A	12/24V	ELECTRONIC 10/45	70 A	45 A	•	•	20 > 1000 Ah	400 A	700 A	•	31 x 36,5 x 65 cm	28,5 kg	GYSTART 724 E		
GYSTART 924.230	025363	230V	16A - 25A	12/24V	ELECTRONIC 10/50	75 A	50 A	•	•	30 > 1100 Ah	650 A	900 A	•	36 x 28 x 78 cm	34 kg	GYSTART 924.230		
GYSTART 1224 T	025394	400V (TRI)	16A	12/24V	3	80 A	60 A	•	•	65 > 1350 Ah	780 A	1200 A	•	42,5 x 34,5 x 71 cm	54,5 kg	GYSTART 1224 T		

TESTERS

TRADITIONAL



TBP 100
Ref 055131

TBP 500
Ref 055148

12V

ELECTRONIC

6V - 12V



BT 111 DHC
Ref 055155

BT 222 DHC
Ref 055216

BT 280 DHC
Ref 055261



RT 002 DHC
Ref 055230

GESTION LOGICIELLE
DE LA BATTERIE
BATTERY MANAGEMENT
SOFTWARE
SOFTWARE BATTERIE
MANAGEMENT



RT 777 DHC
Ref 055247



BT 501 DHC
Ref 055209

7
LANGUAGES
SPRACHEN

PRINTERS
DRUCKER

STANDARD
57mm (W)

BT 501 DHC
x2 (included)
Ref. 056220

RT 777 DHC
x1 (included)
Ref. 056237

				TEST			PRINT PAPER	DIGITAL	RESULT	TEMPERATURE COMPENSATION		
				BATTERY A	BATTERY V	CHARGING & STARTING SYSTEM VEHICLE						
TBP 100	<i>traditional</i>	055131	6-12 V	20>100 Ah	•	•	12V	—	—	5/10s	15 min	1,5
TBP 500	<i>traditional</i>	055148	12 V	10>160 Ah	•	•	12V	—	—	15s	15 min	8
BT 111 DHC	<i>electronic</i>	055155	12 V	20>150 Ah	•	min 7 V	—	•	1s	instant	—	0,25
BT 222 DHC	<i>electronic</i>	055216	12 V	20>150 Ah	•	min 7 V	12V	—	•	1s	instant	0,25
BT 280 DHC	<i>electronic</i>	055261	12 V	4>150 Ah	•	min 4,5 V	12V	—	•	1s	instant	0,25
RT 002 DHC	<i>electronic</i>	055230	6-12 V	7>230 Ah	•	min 1,5 V	12V 24V	—	•	1s	instant	0,8
BT 501 DHC	<i>electronic</i>	055209	6-12 V	7>230 Ah	•	min 1,5 V	12V 24V	•	•	1s	instant	0,4
RT 777 DHC	<i>electronic</i>	055247	6-12 V	7>230 Ah	•	min 1,5 V	12V 24V	•	•	1s	instant	0,7

Recommendation	Test		PRINT PAPER					
	batteries/Battery/ Ladegeräte	Circuit alternateur/ Alternator Circuit/ Lichtmaschinen Schaltkreis						
TBP 100	6V 12V	12V	—		20 > 100 Ah			
TBP 500	12V	12V	—		10 > 160 Ah			
BT 111 DHC	12V	—	—		20 > 150 Ah			
BT 222 DHC	12V	12V	—		20 > 150 Ah			
BT 280 DHC	12V	12V	—		4 > 150 Ah			
RT 002 DHC	6V 12V	12V 24V	—		7 > 230 Ah			
BT 501 DHC	6V 12V	12V 24V	•		7 > 230 Ah			
RT 777 DHC	6V 12V	12V 24V	•		7 > 230 Ah			

BOOSTERS + POWER SUPPLY

WU

Floating Process
Charge 100%

p. 35

1 000 A 12V

GYSPACK ONE

Ref. 025073

1V/C 300 A



1 250 A 12V

GYSPACK AUTO/ GYSPACK 400

1V/C 480 A

Ref. 026230

Ref. 025424

Ref. 025455



Power Supply
18 Ah · 12V DC



1 250 A 12V

GYSPACK AIR

Ref. 026322

Ref. 025431

1V/C 480 A

Isolated clamps
500 A
1,1 m
ø 25 mm²



Power Supply
18 Ah · 12V DC



+ Compressor

Air Kit
included
4 bars



SELECTION

P. 34

1 750 A 12V

GYSPACK PRO

Ref. 026155

WU

p. 35



Power Supply
22 Ah · 12V DC

AUTOMATIC
CHARGER
Power in
12V



included

Isolated clamps
500 A
1,1 m
ø 25 mm²



2 500 A 12V

GYSPACK 750

Ref. 026179

1 REGULATED
IUoU
FAST CHARGE

p. 35



Power Supply
26 Ah · 12V DC

AUTOMATIC
CHARGER
Power in
12V



included

Isolated clamps
600 A
1,3 m
ø 25 mm²



3 200 A 12V

1 600 A 24V

GYSPACK TRUCK

Ref. 025448

1 REGULATED
IUoU
FAST CHARGE

p. 35




Power Supply
44 Ah · 12V DC

AUTOMATIC
CHARGER
Power in
12V



included

Isolated clamps
600 A
1,8 m
ø 25 mm²



GYSPACK 750
GYSPACK TRUCK

AUTOMATIC
CHARGER
Power in
230V/12V

Ref. 054684



Fuses 200 A x2
GYSPACK 750
Ref. 054547

Fuse 300 A x2
GYSPACK TRUCK
Ref. 054561



Après chaque utilisation
After each use
Nach jeder Anwendung

	12V	START	ON/OFF	TEST	OK	Box	Weight
	Inside	1V/C	Cranking CC	Peak Battery			
GYSPACK PRO	22 Ah	12V 600 A	1100 A	1750 A	•	24 x 17 x 285 cm	5,8 kg
GYSPACK 750	26 Ah	12V 750 A	1450 A	2500 A	•	33 x 14 x 35 cm	7 kg
GYSPACK TRUCK	2 x 22 Ah	12V 750 A / 24V 650 A	1450 A / 1300 A	3200 A / 1600 A	•	35,5 x 19,5 x 43 cm	10 kg

BOOSTERS
CAR + TRUCK



p. 35

SELECTION P. 34

1 800 A	12V
GYSPACK 650	

Ref. 026254



1 096 700

1V/C 640 A

3 100 A	12V
GYSPACK 810	

Ref. 026278




1 096 701

1V/C 830 A






3 600 A	12V
1 800 A	24V ★
STARTPACK 12.24	


Ref. 026285



6 200 A	12V
3 100 A	24V ★★ ★
GYSPACK PRO 12.24	

Ref. 026452



																	
		Inside		1V/C	Cranking CC	Peak Battery							Memory	Fuse	Fuse		
GYSPACK 650	026254	16 Ah	12V	640 A	1200 A	1800 A	●		3 A	●	●	→ 12V DC	15 A	200 A	2 x 1,4 m ø 25 mm²	23 x 35 x 35 cm	13 kg
GYSPACK 810	026278	30 Ah	12V	830 A	1700 A	3100 A	●		3 A	●	●	→ 12V DC	15 A	2 x 200 A	2 x 1,8 m ø 35 mm²	18 x 38 x 31 cm	16,6 kg
STARTPACK 12.24	026285	2x16 Ah	12V	900 A	1700 A	3600 A	●		7 A	●	●	—	20 A	2 x 200 A	2 x 1,8 m ø 35 mm²	21 x 35 x 56 cm	23,5 kg
GYSPACK PRO 12.24	026452	2x30 Ah	12V	700 A	1350 A	1800 A	●		7 A	●	●	—	20 A	2 x 200 A	2 x 1,8 m ø 35 mm²	21 x 35 x 56 cm	23,5 kg
			24V	1300 A	2400 A	6200 A	●		7 A	●	●	—	20 A	2 x 200 A	2 x 2 m ø 50 mm²	12 x 64 x 97cm	45,5 kg
			24V	1200 A	2250 A	3100 A	●		7 A	●	●	—	20 A	2 x 200 A	2 x 2 m ø 50 mm²	12 x 64 x 97cm	45,5 kg

12V

i Recommendation	
GYSPACK 650	
GYSPACK 810	

24V

i Recommendation	
GYSPACK TRUCK	
STARTPACK 12.24	★
GYSPACK PRO 12.24	PRO ★★ ★

BOOSTER
TRUCK & BUS

CHARGER
AUTOMATIC X2




p. 35

12/24V

ENERGY STATION

Ref. 026148



MEMORY
AUTO SAVE

SAUVEGARDE MÉMOIRE OBD / Memory auto save
/ Speicherschutz / Salvaguardia memorias
/ Salvaguardas de memória / Αυτόματα αποθήκευση ρυθμίσεων
/ Сохранение настроек/ 记忆储存器

GYSPACK OBD

Ref. 054998

Ref. 055001



OBD



7 Ah
INSIDE




Après chaque utilisation
After each use
Nach jeder Anwendung


INSIDE	MEMORY SAVER			
12V 7 Ah	OBD < 4 A	< 4 A	25 x 18 x 25 cm	3 kg



< 4A



Batteries non fournies
Batteries not provided
Ohne Batterie



OPTION
Kit roues mousse polyuréthane
/Wheel kit/Räder-Kit
Ref. 053212



Après chaque utilisation
After each use
Nach jeder Anwendung



Recommendation

ENERGY STATION

12V 24V

ENERGY STATION

026148

START
selon batteries
/according to battery

12V 24V

CHARGE
min > max
35 > 225 Ah

Moyen / Average
(EN 60335)
2 x 15 A

Efficace
/ RMS
2 x 22 A

Fuse
2 x 30 A

70 x 62 x 92 cm


36 kg + batteries

2 x 2,5 m - ø 35 mm²

SAUVEGARDE MÉMOIRE
/ Memory auto save
/ Speicherschutz

230V/12V

Ref. 055018



JUMPER CABLES
CONSUMER



Ref.			
056367	200 A	2,5 m	7 mm ²

ISOLATED CLAMPS



Ref.			
056398	200 A	2,8 m	10 mm ²
056411	320 A	3 m	16 mm ²
056428	500 A	3,5 m	25 mm ²
056442	700 A	4,5 m	35 mm ²

ISOLATED CLAMPS & LED



Ref.			
056374	300 A	3 m	16 mm ²
056381	500 A	3,5 m	25 mm ²

JUMPER CABLES
PROFESSIONAL

ISOLATED CLAMPS

PRO

BRASS CLAMPS

SUPER PRO

PINCES ISOLÉES - INSULATED CLAMPS - ISOLIERTE KLEMMEN - Pinzas aisladas - Garras aisladas
• Geïsoleerde klemmen • Μονωμένοι ακροδέκτες • Изолированные зажимы • 绝缘充电夹



MADE IN P.R.C



Ref.			
056312	200 A	2,8 m	10 mm ²
056329	320 A	3 m	16 mm ²
056336	500 A	3,5 m	25 mm ²
056343	700 A	4,5 m	35 mm ²

PINCES LAITON, NON ISOLÉES - Brass clamps, NOT INSULATED - Messingklemmen, nicht isoliert - pinzas de latón, no aisladas
• Koperen klemmen, niet geïsoleerd • Garras bronce, latão isoladas • Ακροδέκτες χαλκού χωρίς μόνωση • ЛАТУННЫЕ ЗАЖИМЫ, НЕИЗОЛИРОВАННЫЕ
• 黄铜夹, 无绝缘



MADE IN P.R.C



Ref.			
056206	320 A	3 m	16 mm ²
564015	500 A	3 m	25 mm ²
056404	700 A	4,5 m	35 mm ²
056602	1000 A	5,1 m	50 mm ² (100% Cu)



MADE IN FRANCE

PINCES ISOLÉES - INSULATED CLAMPS - ISOLIERTE KLEMMEN - Pinzas aisladas - Garras aisladas
• Geïsoleerde klemmen • Μονωμένοι ακροδέκτες • Изолированные зажимы • 绝缘充电夹



Ref.			
056541	700 A	4,5 m	35 mm ²



MADE IN FRANCE



Ref.			
056619	1000 A	5 m	50 mm ²



ANTI-ARC
PROTECTION
x2

POWER INVERTER

12V > 230V

CONVERGYS 150

Ref. 027015

Ref. 027008



CONVERGYS 300

Ref. 027053


Ref. 027046



PSW 8300

Ref. 027114

Ref. 027107



PSW 8600

Ref. 027169

Ref. 027152



Conversion Chart / Table:

horse power to watts	watts to horse power
hp = W	W = hp
0,1 = 73,5	100 = 0,1360
0,2 = 147,1	200 = 0,2719
0,3 = 220,6	300 = 0,4079
0,4 = 294,2	400 = 0,5438
0,5 = 367,7	500 = 0,6798
1 = 735,5	1000 = 1,3596
2 = 1471,0	2000 = 2,7192
3 = 2206,5	3000 = 4,0789
4 = 2942,0	4000 = 5,4385

PSW 81500

Ref. 027220

Ref. 027190



	Power	Peak power	Pure Sin Wave	Optimum Efficiency	Input DC	Output AC	Output USB DC	max 150W	Universal	Input	Output	Weight
CONVERGYS 150	150W	300W	—	90,5 %	12V	230V	5V - 500 mA	•	—	—	6 x 10 x 5 cm	0,34 kg
CONVERGYS 300	300W	600W	—	85 %	12V	230V	5V - 500 mA	•	•	—	10 x 15 x 6 cm	0,85 kg
PSW 8300	300W	600W	•	85 %	12V	230V	5V - 500 mA	—	•	•	18 x 18 x 7 cm	1,2 kg
PSW 8600	600W	1200W	•	85 %	12V	230V	5V - 500 mA	—	•	•	18 x 20 x 7 cm	2,3 kg
PSW 81500	1500W	3000W	•	85 %	12V	230V	5V - 500 mA	—	•	•	18 x 31 x 7 cm	4 kg
MSW 82 000 NEW	2000W	4000W	•	80 %	24V	230V	5V - 500 mA	—	cables	•	35 x 20 x 9,8 cm	5,4 kg

CONVERGYS 150

CONVERGYS 300

PSW 8300

PSW 8600

PSW 81500

PSW 82 000 **NEW**

150W

300W

300W

600W

1500W

2.000W

DHC 54E STATION MULTICHARGE POUR BATTERIES - Multi charge station for batteries - multi-ladestation für starter-batterien

Charge automatique • Automatic charge • Automatischer Ladevorgang

4 x 5A 12V (liquid/gel)
5 étapes • 5 steps • 5 Schritte
Pulse/Boost/Egalisation/100%/Floating
Maintenance/Zusatzhilfskit



10/100 Ah


Multicharge Station DHC 54E

Ref. 025097



KIT SOLAIRE DE MAINTIEN DE CHARGE - Solar powered charger - Solarpanel zur Ladeerhaltung - Kit solar de mantenimiento de carga - Солнечная панель для поддержания заряда в наборе с аксессуарами

Ref. 029163

NEW
11/2013

PINCES - Clamps • Klemmen • Pinzas • Garras • Ακροδέκτες • Зажимы • 充电夹

40 A



• (x2) Ref.053106

200 A



• Ref.053502 • Ref.053403

300 A



• Ref.053700 • Ref.053601

600 A



• Ref.053779 • Ref.053786

850 A



• Ref.053816 • Ref.053793

COSSES BATTERIE - Battery Terminal - Polklemmen - Terminales batería - Accupool - Terminais de bateria - Πόλος μπαταρίας - Контакты аккумуляторной - батареи - 电池端子

	ø 10 mm / 35 mm ²	ø 13 mm / 50 mm ²	ø 16 mm / 70 mm ²
x1			
+			
-			
+	x25 Ref.054431	x25 Ref.054332	x25 Ref.054417
-	x25 Ref.054448	x25 Ref.054349	x25 Ref.054424
	x25 Ref.054356	x25 Ref.054363	x25 Ref.054370
	x25 Ref.054387		

Quick Connector
ø 10 mm / 50 mm²
I max = 1000 A
Ref. 054455



FUSIBLES - Fuses - Sicherungen - Fusibles - Zekeringen - Fusíveis - Ασφάλειες - Плавкие предохранители - 保險絲

10 A : 054530	15 A : 054493	20 A : 054509	25 A : 054516	30 A : 054523	40 A : 054554
x10					
for Gystart & Prostart (before July 2007)	100A : 054486				
x10					
for Gystart & Prostart (after July 2007)	200A : 054547	300A : 054561			
x2					

AUTRES - Others - Andere - Otros - Outros - Άλλα - Разное - Другое par Разное - 其他

Protection anti-arc 12V • Anti-arc protection 12V • Lichtbogenschutz 12V
• Protección anti-arco 12V • Piekspanningsbeveiliging 12V
• Protecção anti-faísca 12V
• Αντι-σπινθηρική προστασία 12V
• Защита против дуги 12В
• 12V 抗电弧保护

Ref. 041318



Pèse acide antigel • Acidimeter (PH Meter)
• Säure/Frostschutzmittel-Tester • Acido densímetro anticongelante
• Zuurweger • Medidor de PH (ácido)
• Μετρητής οξύτητας (PH) • Ацидиметр (pH-метр) • 防冻酸度计

Ref. 054103



CHOOSE YOUR BOOSTER

CHOISISSEZ VOTRE BOOSTER

	12 V							12 - 24 V			
	GYSPACK ONE	GYSPACK AUTO	GYSPACK AIR	GYSPACK PRO	GYSPACK 650	GYSPACK 750	GYSPACK 810	GYSPACK TRUCK	STARTPACK 12.24	GYSPACK PRO 12.24	ENERGY STATION
	025073	026230 025455	026322	026155	026254	026179	026278	025448	026285	026452	026148
	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V
	24V							24V	24V	24V	24V
1V/C	300 A	480 A	480 A	600 A	640 A	750 A	830 A	750 (12V)	900 A (12V)	1300 A (12V)	
								650 (24V)	700 A (24V)	1200 A (24V)	
CC	600 A	900 A	900 A	1100 A	1200 A	1450 A	1700 A	1450 A (12V)	1700 A (12V)	2400 A (12V)	
								1300 A (24V)	1350 A (24V)	2250 A (24V)	
PEAK	1000 A	1250 A	1250 A	1750 A	1800 A	2500 A	3100 A	3200 A (12V)	3600 A (12V)	6200 A (12V)	
								1600 A (24V)	1800 A (24V)	3100 A (24V)	
12V	12 Ah	18 Ah	18 Ah	22 Ah	16 Ah	26 Ah	30 Ah	2 x 22 Ah	2 x 16 Ah	2 x 30 Ah	—
	—	—	•	•	•	•	•	•	•	•	—
	—	•	•	•	•	•	•	—	—	—	•
	outside 0,5 A	outside 0,5 A	outside 0,5 A	outside 0,5 A	inside 2,5 A	outside 2 A	inside 2,5 A	outside 2 A	inside 7 A	inside 7 A	inside 2 x 15 A
		12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	—	—	—
	—	—	•	—	—	—	—	—	—	—	—
	—	—	•	•	—	•	—	•	—	—	—
	0,5 m ø16 mm ²	0,5 m ø16 mm ²	1,1 m ø25 mm ²	1,1 m ø25 mm ²	1,4 m ø25 mm ²	1,3 m ø25 mm ²	1,8 m ø35 mm ²	1,8 m ø25 mm ²	1,8 m ø35 mm ²	1,8 m ø35 mm ²	2,5 m ø50 mm ²
	22 x 24 x 15	33 x 14 x 35	34 x 20 x 43	34 x 20 x 43	33 x 20 x 33	33 x 16 x 38	33 x 20 x 33	35 x 19 x 44	17 x 33 x 48	57 x 34 x 94	70 x 62 x 92
	6 kg	7 kg	8,9 kg	7,9 kg	11 kg	13 kg	15 kg	18 kg	23 kg	31 / 40 kg	36 kg +



ATTENTION HORS UTILISATION
Laisser le chargeur branché
en permanence.

CAUTION ON STAND BY
Keep your GYSPACK connected to the mains supply.

ACHTUNG AUSSER BETRIEB
Lader dauernd angeschlossen lassen.

ATTENTION CUANDO ESTA APAGADO
Dejar el cargador conectado permanentemente.

OPGELET BIJTEN GEBRUIK
Laat de lader onafgebroken aangesloten.

★
MINI PRO


★★★
PRO

★★★
UNIVERSAL PRO

BATTERIES DE DÉMARRAGE - Automotive batteries - Starterbatterien - Baterías de arranque - Automotive accu's
- Baterías de Automóvil - Μπαταρίες οχημάτων - Пусковые батареи - 汽车启动电池

TRADITIONAL

W



Recommendation

LIQUID Calcium Silver AGM START/STOP (A) GEL Sealed OPTIMA maXXima


UNIVERSAL MAINTENANCE EASY USE HIGH TECH



ENERGY
Consumer
/Tourisme
p.4

AUTOMATIC


W2



Recommendation


LIQUID Calcium Silver AGM START/STOP (A) GEL Sealed OPTIMA maXXima

UNIVERSAL MAINTENANCE EASY USE HIGH TECH



STARTUP 80
Consumer
/Tourisme
p.5

WU



Recommendation


LIQUID Calcium Silver AGM START/STOP (A) GEL Sealed OPTIMA maXXima

UNIVERSAL MAINTENANCE EASY USE HIGH TECH



TCB
Consumer
/Tourisme
p.4-5

WUoU



Recommendation

LIQUID Calcium Silver AGM START/STOP (A) GEL Sealed OPTIMA maXXima

UNIVERSAL MAINTENANCE EASY USE HIGH TECH




WATTMATIC
Professional p.11

BOOSTER
Professional p.24-26

AUTOMATIC FAST CHARGE

IWUoU



Recommendation


LIQUID Calcium Silver AGM START/STOP (A) GEL Sealed OPTIMA maXXima

UNIVERSAL MAINTENANCE EASY USE HIGH TECH



BATIUM
Professional p.12-13

I.I.I



Recommendation


LIQUID Calcium Silver AGM START/STOP (A) GEL Sealed OPTIMA maXXima

UNIVERSAL MAINTENANCE HIGH TECH



GYSTECH
Consumer
/Tourism
p.6-8

I REGULATED IUoU FAST CHARGE



Recommendation

LIQUID Calcium Silver AGM START/STOP (A) GEL Sealed OPTIMA maXXima


UNIVERSAL MAINTENANCE EASY USE HIGH TECH



GYSFLASH 4A/7A
Professional p.7

GYSFLASH 75-12/70-24 HF
Professional p.16-17

I REGULATED IUoU FAST CHARGE



Recommendation

LIQUID Calcium Silver AGM START/STOP (A) GEL Sealed OPTIMA maXXima

UNIVERSAL MAINTENANCE EASY USE HIGH TECH




GYSFLASH 30.12/30.24 HF
Professional p.15-16

BATIUM 25/24
Professional p.12

BATTERIES DE TRACTION - Traction batteries - Traktionsbatterien - Baterías de tracción - Tractieaccu's - Baterías de Tracción
- Μπαταρίες έλξεως - Тяговые батареи - 牵引用铅酸蓄电池

AUTOMATIC FAST CHARGE

IUoU




Recommendation

Traction batteries ★★★
High Technologie ★




GYSFLASH 70-24 HF
Professional p.16-17


BATIUM 25/24
Professional p.12



24V 150Ah
(GYS Recommendation : BATIUM 15/24 - 25/24)



12V 360Ah
(GYS Recommendation : GYSFLASH : 75/12HF - 30 HF)



24V 290Ah
(GYS Recommendation :
CA 350 - BATIUM 25/24 - GYSFLASH 30.24 HF)

Conversion Chart / Table:

horse power to watts	watts to horse power
hp = W	W = hp
0,1 = 73,5	100 = 0,1360
0,2 = 147,1	200 = 0,2719
0,3 = 220,6	300 = 0,4079
0,4 = 294,2	400 = 0,5438
0,5 = 367,7	500 = 0,6798
1 = 735,5	1000 = 1,3596
2 = 1471,0	2000 = 2,7192
3 = 2206,5	3000 = 4,0789
4 = 2942,0	4000 = 5,4385



GYS France

BP 4159
53941 Saint-Berthevin
Laval cedex France
Fax : +33 (0)2 43 68 35 21

www.gys.fr
E-mail : contact@gys.fr

GYS Germany

Professor-Wieler-Straße 11
52070 Aachen - Deutschland
Tel : +49 (0) 241 / 189-23-710
Fax : +49 (0) 241 / 189-23-719
www.gys-schweissen.com
E-mail : aachen@gys.fr

GYS UK

Unit 2
Spartan Close
Tachbrook Park
Warwick - United Kingdom - CV34 6RS
Tel : +44 (0) 1926 338 609
Fax : +44 (0) 1926 429 764
www.gys-welding.com
E-mail : uk@gys.fr

GYS India

20, Huzur Road - Near Anna Statue
Coimbatore - 641018
Tamil Nadu - India
Tel : +91. 88708. 71111
E-mail : r.samal@gys.fr


GYS China

Lot N°15
6666 bd Songze
201706 Qingpu Shanghai - China
Tel : +86 (21) 6221 4461
Fax : +86 (21) 5226 0067
www.gysasia.com
E-mail : contact@gys-china.com.cn

Bao Zhi Long Electrical Equipment (JV GYS)

Room: 203C
Building: N°1
N°518 Shen Wang Road
Minhang District Shanghai - China
Tel1 : +86 (21) 52217650
Tel2 : +86 (21) 52217651
Tel3 : +86 (21) 52217652
Fax : +86 (21) 52217653
www.bzl-china.com
E-mail : mz@bzl-china.com

International Events



Distributed by :

