

- Welding unit with inverter technology and microprocessor control
- The arc dynamic of the product is unique enabling the highest standard of welding result
- Can be used with all types of electrodes: rutile, stainless steel & cast iron

**MMA :**

- ✓ Instant and easily controlled start
- ✓ Constant welding power
- ✓ Tolerant to current fluctuations or to the arc length
- ✓ High penetration and perfect arc stability

REF.029958

Delivered in cardbox with

Earth cable (1.6m/ø10mm<sup>2</sup>)  
Electrode holder (1.6m/ø10mm<sup>2</sup>)

REF.0 29941






Delivered in suitcase with

Earth cable (1.6m/ø10mm<sup>2</sup>)  
Electrode holder (1.6m/ø10mm<sup>2</sup>)  
Hand mask  
Chipping hammer

This welding unit offers the following advantages :

- ✓ **ARC FORCE** : Instantaneous increase of the current in difficult welding situation
- ✓ **HOT START** : Increased power at start
- ✓ **ANTI STICKING** : Prevents the electrode sticking

 EN 60974-1

 50/60Hz				<b>I<sub>2</sub></b>								EN60974-1 (40°C)		 U <sub>0</sub>	 cm kg		 Protected & compatible POWER GENERATOR (+/- 10%)	
TIG	MMA	ø1,6	ø2	ø2,5	ø3,2	ø4	ø5	I <sub>A</sub> (60%)	X% (I <sub>2</sub> max)									
10A ▽ 80A	10A ▽ 80A	62	50	20	-	-	-	31A	6%	85V	10x18x24cm 2,5kg	3kW	3,7kVA					